



van den Hul®
A Sound Connection

D - 352 HYBRID (Halogen Free)

This twin lead brown metallic coloured speaker cable is designed to provide a very high transfer quality at a moderate price.

Each lead is made of 296 x 0.15 mm. Matched Crystal (MC) high purity OFC strands with a dense and very pure silver coating.

Covering the two conductors an extra layer saturated with Linear Structured Carbon® is applied to improve the sonic performance and to transform the radiated magnetic field into an audio signal again.

The cable jacket is made of our HULLIFLEX® 3, a very flexible and mechanically superb insulation material.

The resistance per lead is: 0.34 Ohm/100 meter.

Total metal cross-section area for each conductor is 5.23 mm², equalling AWG 10. The capacitance between the 2 leads is: 32.5 pF/meter.

The plus and minus leads are different in jacket-shape with printing in the flat middle section. Both properties are easy polarity-finders.

Type printing at 25 cm. (10") distance makes cutting of specified lengths very easy.



Our 4.0 mm. $\bar{\text{c}}$ cable entrance diameter Bus type Universal Speaker Connectors and our DIY Screw-On Speaker Connectors are excellently suited for the D - 352 HYBRID.

Packing conditions: 50 meters per reel with a total shipping weight of 10.4 kg. incl. the packing box with external dimensions in mm.: 310 x 310 x 290.

Related Articles & Papers:

[Carbon Links - HI-fi News Jan 2000.pdf](#)

Cable Type:	Twin conductor
Conductor Material:	HYBRID: High purity dense Silver coated high purity Matched Crystal OFC + Linear Structured Carbon® saturated layer(s)
Design Purpose/ Application Area(s):	Loudspeaker cable
Eff. Conductor Ø/Eq. AWG No./Strands:	2x(5.23 mm ² / AWG 10 / 296)
External Diameter / -Dimensions:	21.0 mm. wide; 6.5 mm. thick
Resistance 20 °C / 68 °F:	0.34 Ohm/100 m.
Capacitance:	32.5 pF/m.
Insulation / Dielectric Strength / Test Voltage:	HULLIFLEX® 3 / 300 Vrms min.
Connector Types Suitable:	Our 4.0 mm. $\bar{\text{c}}$ cable entrance diameter Bus type Universal Speaker Connectors or our DIY Screw-On Speaker Connectors; Both custom mountable on ordered lengths.
Standard Sales Units / - Lengths:	50 m. reels; With connectors mounted to specifications: any length; Without connectors: please consult your van den Hul dealer or the van den Hul distributor in your country.
Jacket Colours Available:	Brown metallic
Remarks:	Self mounting of connectors is not advised since special soldering equipment is required; Our custom connector mounting service is available.